

## Tapered roller bearing 32934-TIMKEN - 32934-TIMKEN

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32934-timken>

**TAPERED ROLLER BEARINGS**  
SINGLE-ROW • IsoClass

**IsoClass**

Bearing Dimensions			Load Ratings						Part Number	
Bore d	O.D. D	Width T	Dynamic <sup>(1)</sup> C <sub>1</sub>	Factor <sup>(2)</sup> e	Dynamic <sup>(3)</sup> C <sub>2</sub>	Factor <sup>(3)</sup> K	Static C <sub>0</sub>	Assembly Inner/Outer		
mm	mm	mm	N		N	N	N			
in	in	in	lbf		lbf	lbf	lbf			
170.000	230.000	38.000	35000	0.30	10200	1300	62000	20204		
6.6929	9.0551	1.4961	7890		22700	1300	140000			

  

Mounting Dimensions										Geometry Factors			Bearing Weight	
Shaft					Housing									
Width B	Width C	ER Co. a <sup>(1)</sup>	Max Shaft Fillet Radius R <sup>(1)</sup>	Backing Shoulder Dia. d <sub>s</sub>	Max Housing Fillet Radius r <sup>(1)</sup>	Backing Shoulder Dia. D <sub>s</sub>	Cage A <sub>1</sub> <sup>(1)</sup>	A <sub>2</sub> <sup>(1)</sup>	A <sub>3</sub> <sup>(1)</sup>	G <sub>1</sub>	G <sub>2</sub>	C <sub>2</sub>	kg	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	lb	
38.000	36.000	2.0	2.5	175.0	152.0	2.0	22.0	215.0	2.0	4.0	519.3	165.0	0.1005	4.40
1.4961	1.4173	0.11	0.10	7.00	6.02	0.08	0.78	8.48	0.08	0.16			0.11	

### PRODUCT FEATURES

Brand	TIMKEN
N° Ean13	3663952354088
Inside diameter	170 mm
Outside diameter	230 mm
Thickness	38 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE