


## Drawn cup roller bearing TAW6045-Z-IKO - TAW6045-Z-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/drawn-cup/taw6045-z-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**



Shaft dia. mm	Identification number									
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained	Mass (Ref.) g
60	<b>TAW 6045 Z</b>	270	—	—	—	—	—	—	—	—

Boundary dimensions mm	Standard reporting dimensions mm						Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring			
	F <sub>w</sub>	D	C	f <sub>2</sub> Max.	Shaft dia. mm	Housing bore dia. mm							
60	72	45	3.4	60.000	59.981	72.018	71.988	—	—	85 400	193 000	5 000	IRT 5045

Note(\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 80% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952357423
Inside diameter	60 mm
Outside diameter	72 mm
Thickness	45 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE