


Needle roller bearing GBR263516-IKO - GBR263516-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/gbr263516-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
Without Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number	Mass (ref.) g	Boundary dimensions mm(inch)			Standard mounting dimensions mm ⁽¹⁾	
			F _o	D	C	D _s Max.	r _{as} max
41.275 (1 5/8)	GBR 263516	180	41.275 (1 5/8)	55.562 (2 1/8)	25.400 (1)	50.5	0.6
Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
N	N	rpm					
56 600	105 000	3 500					

Notes: (1) Maximum permissible corner radius of the housing.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remarks: 2. The outer ring has an oil groove and an oil hole.
3. No grease is pre-applied. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952377803
Inside diameter	41.275 mm
Outside diameter	55.562 mm
Thickness	25.4 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE