


## Needle roller bearing RNA4900-U-IKO - RNA4900-U-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/rna4900-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_a$ (1)
<b>14</b>	---	<b>RNA 4900U</b>	---	---	16.3	14	22	13	0.3
Standard rounding dimension $D_s$ Max. mm	N	N	N	N					
Basic dynamic load rating $C$ Max. mm	8 080	8 490	8 490	14 000					
Basic static load rating $C_0$ Max. mm	N	N	N	N					
Allowable rotational speed (2)	N	N	N	N					

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952378787
Inside diameter	14 mm
Outside diameter	22 mm
Thickness	13 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE