


Needle roller bearing RNA4907-U-IKO - RNA4907-U-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/rna4907-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		F_w	D	C	r_s (1)
42	—	RNA 4907U	—	—	112	42	55	20	0.6
Standard mounting diameter D_s Max. mm									
	Basic dynamic load rating C	Basic static load rating C_0	Allowable rotational speed (2)						
51	30 100	46 300	4 500						

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379180
Inside diameter	42 mm
Outside diameter	55 mm
Thickness	20 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE