

Needle roller bearing RNA6909-U-IKO - RNA6909-U-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/rna6909-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring

| Shaft dia. mm | Identification number | | | | Mass (Ref) g | Boundary dimensions mm | | | |
|--|---------------------------------------|--|---------------------------------------|------------------|--------------------|---------------------------|-----|-----|-----------|
| | With two seals | With one seal | With two seals | With one seal | | F_w | D | C | r_s (1) |
| 52 | — | — | — | RNA 6909U | 355 | 52 | 68 | 40 | 0.6 |
| Standard mounting dimension D_s Max. mm | | | | | | | | | |
| | Basic dynamic load rating C N | Basic static load rating C_0 N | Allowable rotational speed (2) rpm | | | | | | |
| 64 | 66 600 | 127 000 | 3 500 | | | | | | |

Notes: (1) Minimum allowable value of chamfer dimension r .
(2) Allowable rotational speed applies to grease lubrication.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952379319 |
| Inside diameter | 52 mm |
| Outside diameter | 68 mm |
| Thickness | 40 mm |
| Packaging | 1 |

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE