


Needle roller bearing RNA49-58-UU-IKO - RNA49-58-UU-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/rna49-58-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm		
	With two seals	With one seal	With two seals	With one seal		F _w	D	C ⁽¹⁾
65	RNA 49/58UU	—	—	—	275	65	82	25 1
Standard mounting diameter D _s Max. mm	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽²⁾					
77	53 400	89 200	3 000					

Notes:
(1) Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to grease lubrication.
Remarks:
1. The outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379456
Inside diameter	65 mm
Outside diameter	82 mm
Thickness	25 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE