


## Needle roller bearing RNA6912-UU-IKO - RNA6912-UU-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/rna6912-uu-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, Without Inner Ring



Shaft dia. mm	Identification number				Mass (Ref) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		$F_w$	$D$	$C$	$r_1$ (1)
<b>68</b>	—	—	<b>RNA6912UU</b>	—	505	68	85	45	1
Standard mounting diameter $D_s$ Max. mm									
	Basic dynamic load rating $C$	Basic static load rating $C_0$	Allowable rotational speed (2)						
	N	N	rpm						
	80	93 400	186 000	3 000					

Notes: (1) Minimum allowable value of chamfer dimension  $r$ .  
(2) Allowable rotational speed applies to grease lubrication.  
Remarks: 1. The outer ring has an oil groove and an oil hole.  
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952379500
Inside diameter	68 mm
Outside diameter	85 mm
Thickness	45 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE