

Needle roller bearing NA4903-U-IKO - NA4903-U-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/na4903-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
17	—	NA 4903U	—	—	39.5	17	30	13	14

r _s min ⁽¹⁾	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring LRTZ 172214
		Min.	Max.	Max.			
0.3	22	19	21	28	10 300	13 100	8 500

Note(1) Minimum allowable value of chamfer dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381176
Inside diameter	17 mm
Outside diameter	30 mm
Thickness	14 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE