

## Needle roller bearing NA6904-U-IKO - NA6904-U-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/na6904-u-iko>

**IKO**  
**MACHINED TYPE NEEDLE ROLLER BEARINGS**  
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
<b>20</b>	—	—	—	—	<b>NA 6904U</b>	137	20	37	30	31

$r_s$ mm	$F_w$	Standard mounting dimensions mm			Basic static load rating $C_0$ N	Basic dynamic load rating $C$ N	Allowable rotational speed <sup>(1)</sup> rpm	Assembled inner ring
		Min.	Max.	$d_s$				
0.3	25	22	24	35	33 000	44 600	7 500	LRTZ 202531

Note<sup>(1)</sup> Minimum allowable value of diameter dimension  $r$   
 Note<sup>(2)</sup> Allowable rotational speed applies to grease lubrication.  
 Remark: This outer ring has an oil groove and an oil hole.  
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381244
Inside diameter	20 mm
Outside diameter	37 mm
Thickness	31 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE