

Needle roller bearing NA69-22-U-IKO - NA69-22-U-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/na69-22-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm				
	With two seals	With one seal	With two seals	With one seal		d	D	C	B	
22	—	—	—	—	NA 69/22U	153	22	39	30	31

r_s min (¹⁾)	F_w	Standard mounting dimensions mm			Basic static load rating C_0 N	Allowable rotational speed(²⁾) rpm	Assembled inner ring	
		Min.	Max.	Max.				
0.3	28	24	27	37	33 800	52 000	7 000	LRTZ 222831

Note(¹) Minimum allowable value of diameter dimension r
 Note(²) Allowable rotational speed applies to grease lubrication.
 Remark: This roller ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381282
Inside diameter	22 mm
Outside diameter	39 mm
Thickness	31 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE