

Needle roller bearing NA4912-U-IKO - NA4912-U-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/na4912-u-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring

Shaft dia. mm	Identification number				Mass (Ref.) g	Boundary dimensions mm			
	With two seals	With one seal	With two seals	With one seal		d	D	C	B
60	—	NA 4912U	—	—	445	60	85	25	26

r _s min μm	F _w	Standard mounting dimensions mm			Basic static load rating C ₀ N	Allowable rotational speed ⁽²⁾ rpm	Assembled inner ring	
		Min.	Max.	Max.				
1	68	65	66	80	54 500	92 800	3 000	LRTZ 606826

Note(1) Minimum allowable value of diameter dimension r
 (2) Allowable rotational speed applies to grease lubrication.
 Remark: The outer ring has an oil groove and an oil hole.
 2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952381664
Inside diameter	60 mm
Outside diameter	85 mm
Thickness	26 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE