


Needle roller bearing GBRI223520-UU-IKO - GBRI223520-UU-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/gbri223520-uu-iko>

IKO
MACHINED TYPE NEEDLE ROLLER BEARINGS
With Seal, With Inner Ring, Inch Series



Shaft dia. mm (inch)	Identification number		Mass (Ref.) g	Boundary dimensions mm(inch)		
	With two seals	With one seal		<i>d</i>	<i>D</i>	<i>C</i>
34.925 (1 3/8)	GBRI 223520 UU		311	34.925 (1 3/8)	55.562 (2 1/8)	31.750 (1 1/4)

<i>B</i>	<i>F_w</i>	Standard mounting dimensions mm			<i>r</i> _{as max} (1)	Basic dynamic load rating <i>C</i> N	Basic static load rating <i>C₀</i> N	Allowable rotational speed(2) rpm	Assembled inner ring
		Min.	Max.	<i>D_s</i> Max.					
32.000	41.275 (1 5/8)	40.2	40.2	50.5	0.6	56 600	105 000	1 900	LRBZ 222620

Notes (1) Minimum allowable value of chamfer dimension *r*
(2) Allowable rotational speed applies to grease lubrication.
Remark: This outer ring has an oil groove and an oil hole.
2. Bearings with seals on both sides are provided with prepacked grease. Bearings with a seal on one side are not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952383439
Inside diameter	34.925 mm
Outside diameter	55.562 mm
Thickness	31.75 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE