

Needle roller bearing NAU4911-UU-IKO - NAU4911-UU-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nau4911-uu-iko>

IKO

ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**

Full Complement Roller Bearings **[With Seal]**

NAU49-UU
TRU-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ⁽¹⁾ min	J
55	—	NAU 4911UU		385	55	80	25	1	Ø1.5
E _w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _g rpm						
	N	N	3,000						

Notes: ⁽¹⁾ Minimum allowable value of chamfer dimension r
⁽²⁾ Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386232
Inside diameter	55 mm
Outside diameter	80 mm
Thickness	25 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE