


Needle roller bearing NAU4916-UU-IKO - NAU4916-UU-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nau4916-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings [With Seal]
Full Complement Roller Bearings [With Seal]



Shaft dis. mm	Identification number		Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type		d	D	C	r ⁽¹⁾ min	J
80	---	NAU 4916UU	790	80	110	30	1	89.5
E _w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _g rpm					
	N	N		2,000				

Notes^(*)
⁽¹⁾ Minimum allowable value of chamfer dimension r
^(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
 Remarks: 1. The NAU and TRU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
 2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386348
Inside diameter	80 mm
Outside diameter	110 mm
Thickness	30 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE