


Needle roller bearing NAG4917-UU-IKO - NAG4917-UU-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nag4917-uu-iko>

IKO
ROLLER BEARINGS

Caged Roller Bearings **[With Seal]**
Full Complement Roller Bearings **[With Seal]**



NAG49-UU

Shaft dis. mm	Identification number			Mass (Ref.) g	Boundary dimensions mm				
	Full complement type	Caged type			d	D	C	r ⁽¹⁾ min	J
85	NAG 4917UU	—		1 190	85	120	35	1.5	96
E_w	Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed n _g rpm						
110	111 000	200 000	1,500						

Notes: (1) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386485
Inside diameter	85 mm
Outside diameter	120 mm
Thickness	35 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE