


## Needle roller bearing NAS5017-ZZ-NR-IKO - NAS5017-ZZ-NR-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nas5017-zz-nr-iko>

**IKO**  
**ROLLER BEARINGS**  
Roller Bearings for Sheaves



Shaft dia. mm	Identification number				Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type				d	D	D <sub>2</sub>	B	C	C <sub>1</sub>	S
<b>85</b>		<b>NAS 5017ZZNR</b>			2.80	85	130	134.5	60	59	48	5.5
f	c	r <sub>s</sub> mm <sup>(1)</sup>	J	Basic dynamic load rating C N	Static load rating C <sub>0</sub> N	Allowable rotational speed <sup>(2)</sup> rpm						
2.5	2	0.6	101	257 000	446 000	1 200						

Notes: (1) Minimum allowable value of chamfer dimension r.  
(2) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.  
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.  
2. The bearings with seals are provided with prepacked grease.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386911
Inside diameter	85 mm
Outside diameter	130 mm
Thickness	60 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE