


Needle roller bearing NAS5019-ZZ-NR-IKO - NAS5019-ZZ-NR-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nas5019-zz-nr-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
95		NAS 5019ZZNR	3.90	95	145	150.4	67	66	54	6

f	c	r _s mm	J	Basic dynamic load rating	Static load rating	Allowable rotational speed ^(*)
				C	C ₀	rpm
2.5	2.5	0.6	114	312 000	562 000	1 100

Notes: (*) Minimum allowable value of chamfer dimension r.
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAG and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952386959
Inside diameter	95 mm
Outside diameter	145 mm
Thickness	67 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE