


Needle roller bearing NAS5080-UU-IKO - NAS5080-UU-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nas5080-uu-iko>

IKO
ROLLER BEARINGS
Roller Bearings for Sheaves



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						
	Sealed type	Shield type		d	D	D ₂	B	C	C ₁	S
400	NAS 5080UU		265	400	600	—	272	270	—	—

f	c	r _s mm	J	Basic dynamic load rating C N		Allowable rotational speed ^(*) rpm
				C	C ₀	
—	6	2.5	471	4 250 000	10 100 000	250

Notes^(*) Minimum allowable value of chamfer dimension r
(*) Allowable rotational speed applies to grease lubrication. Considering that the axial load acts under practical operating conditions, up to 1/10 of this value is recommended for actual use.
Remarks: 1. The NAS and NAU series with a bore diameter, d, of 17 mm or less have no oil hole. In others, the outer ring has an oil groove and two oil holes.
2. The bearings with seals are provided with prepacked grease.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952387383
Inside diameter	400 mm
Outside diameter	600 mm
Thickness	272 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE