

Needle roller bearing NBXI1730-IKO - NBXI1730-IKO

<https://www.123bearing.ie/bearing-housing/needle-roller-bearing/needle/nbxi1730-iko>

IKO
COMBINED TYPE NEEDLE ROLLER BEARINGS

Needle Roller Bearings with Thrust Ball Bearing **With Inner Ring**
Needle Roller Bearings with Thrust Roller Bearing **With Inner Ring**

Shaft dia. mm	Identification number						d	D	D _i
	Mass (Ref.) g	With dust cover	Mass (Ref.) g	Mass (Ref.) g	With dust cover	Mass (Ref.) g			
17	---	---	---	NBXI 1730	108	---	17	30	35

Boundary dimensions mm										Basic dynamic load rating C N	Basic static load rating C ₀ N	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring			
D ₂	L	B	H	I ₁	r _{max}	r _{min}	d ₄	d ₅	d							
36	30	20.5	10	10.5	0.3	0.3	20	33	19	17	600	19 000	25 400	48 700	11 000	LRT 172020

Notes⁽¹⁾ Minimum allowable value of chamfer dimension r.
(2) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 70% of this value is allowable in the NAX series, and a maximum of 25% of this value is allowable in the NEX series.
Remarks: 1. The outer ring has an oil groove and an oil hole.
2. Grease is not prepacked. Perform proper lubrication.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952390789
Inside diameter	17 mm
Outside diameter	30 mm
Thickness	30 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE