

GE Rod end
SB6510555-IKO - SB6510555-IKO

<https://www.123bearing.ie/bearing-housing/rod-end/ge/sb6510555-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree
			d	D	B	C	d _k	r ₁ mm ⁽¹⁾	
65	SB 6510555	2.05	65	105	55	47	94	0.6	5
Mounting dimensions mm		Dynamic load capacity C _d N	Static load capacity C _s N	d _s		D _s			
Min.	Max. ⁽²⁾			Min.	Max.	Min.	Max.		
69.5	76	433 000	2 600 000	100.5	87				

Notes⁽¹⁾ Minimum allowable value of chamfer dimensions r₁ and r₂.
⁽²⁾ When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s.
Remark1: The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2: Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391397
Inside diameter	65 mm
Outside diameter	105 mm
Thickness	55 mm
Type	GE
Weight	2050 g
Lubrication	without
Packaging	-
Standard	No standard

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE