

## GE Rod end SB130A-IKO - SB130A-IKO

<https://www.123bearing.ie/bearing-housing/rod-end/ge/sb130a-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings

Shaft dia. mm	Identification number	Mass (Ref.) kg	Boundary dimensions mm					Permissible tilting angle degree $\alpha$	
			$d$	$D$	$B$	$C$	$d_k$ <sup>(1)</sup> $r_s$ mm		
130	<b>SB 130A</b>	13.8	130	200	110	95	185	1	5
Mounting dimensions mm		Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N						
$d_s$ Min.	Max. <sup>(2)</sup>		$D_s$ Min.	Max.	Min.	Max.			
135.5	148.5	194.5	171	1720 000	10 300 000				

Notes: <sup>(1)</sup> Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
<sup>(2)</sup> When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark: 1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391601
Inside diameter	130 mm
Outside diameter	200 mm
Thickness	110 mm
Type	GE
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE