


GE Rod end GE90ES-2RS-IKO - GE90ES-2RS-IKO

<https://www.123bearing.ie/bearing-housing/rod-end/ge/ge90es-2rs-iko>

IKO
SPHERICAL BUSHINGS
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm							Permissible tilting angle degree	
	Without seals	With seals		d	D	B	C	d_s	r_1 (1)	r_2 (1)	α	α_1
90		GE 90ES-2RS	2.82	90	130	60	50	115	1	1	5	3
Mounting dimensions mm		Dynamic load capacity C_d		Static load capacity C_s								
d_s	D_s			N		N						
Min.	Max.(2)	Max.	Min.	N		N						
95.5	98	124.5	112	564 000		3 380 000						

Notes(1) Minimum allowable value of chamfer dimensions r_1 and r_2 .
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of d_s .
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.
2. Not provided with prepacked grease. Perform proper lubrication for use.

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952391939
Inside diameter	90 mm
Outside diameter	130 mm
Thickness	60 mm
Type	GE
Lubrication	without
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE