


**GE Rod end**  
**GE140ES-2RS-IKO - GE140ES-2RS-IKO**  
<https://www.123bearing.ie/bearing-housing/rod-end/ge/ge140es-2rs-iko>

**IKO**  
**SPHERICAL BUSHINGS**  
Steel-on-steel Spherical Bushings



Shaft dia. mm	Identification number		Mass (Ref.) kg	Boundary dimensions mm						Permissible tilting angle degree		
	Without seals	With seals		$d$	$D$	$B$	$C$	$d_s$	$r_1$ (1)	$r_2$ (1)	$\alpha$	$\alpha_1$
<b>140</b>	<b>GE 140ES-2RS</b>		11.4	140	210	90	70	180	1	1	7	5
Mounting dimensions mm			Dynamic load capacity $C_d$ N	Static load capacity $C_s$ N								
$d_s$	$D_s$				Min.	Max.(2)	Min.	Max.	Min.	Max.	Min.	Max.
145.5	155.5	204.5	176	1 240 000	7 410 000							

Notes(1) Minimum allowable value of chamfer dimensions  $r_1$  and  $r_2$ .  
(2) When Spherical Bushings are used with full tilting angle, the shaft shoulder dimension must be less than the maximum value of  $d_s$ .  
Remark1. The inner ring and the outer ring have an oil groove and two oil holes, respectively.  
2. Not provided with prepacked grease. Perform proper lubrication for use.

**PRODUCT FEATURES**

Brand	IKO
N° Ean13	3663952392011
Inside diameter	140 mm
Outside diameter	210 mm
Thickness	90 mm
Type	GE
Weight	11127 g
Lubrication	without
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE