

# Tapered roller bearing 33118-JR-JTEKT - 33118-JR-KOYO

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/33118-jr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)				Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.		
90	150	45	45	35	258	413	2 500	3 300	33118JR	

  

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.	r <sub>2a</sub> min.	r <sub>2a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
30E	35.4	102	100	140	130	144	7	10	2	2	0.40	1.51	0.83	3.13	

## PRODUCT FEATURES

Brand	JTEKT
N° Ean13	4549250250507
Inside diameter	90 mm
Outside diameter	150 mm
Thickness	45 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE