

# Tapered roller bearing 32952-JR-JTEKT - 32952-JR-KOYO

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/32952-jr-koyo>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |            | Bearing No. <sup>1)</sup> |                |                      |      |
|--|--------------------|--------------------------|----------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                    | C <sub>r</sub>          | C <sub>0r</sub>      | C <sub>90</sub>      | C <sub>100</sub>     | Grease lub.                          | Oil lub.   |                           |                |                      |      |
| 260                                    | 360                | 63.5                     | 63.5                 | 48                   | 3                       | 2.5                  | 741                  | 1550                 | 830                                  | 1100       | 32952JR                   |                |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                      |                         |                      |                      |                      |                                      | Constant e | Axial load factors        |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | d <sub>2a</sub> min. | d <sub>2a</sub> max.    | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min. | r <sub>1a</sub> max.                 |            | Y <sub>1</sub>            | Y <sub>0</sub> |                      |      |
| 3EC                                    | 69.6               | 274                      | 279                  | 348                  | 328                     | 347                  | 11                   | 15.5                 | 2.5                                  | 2          | 0.41                      | 1.48           | 0.81                 | 18.9 |

## PRODUCT FEATURES

|                  |               |
|------------------|---------------|
| Brand            | JTEKT         |
| N° Ean13         | 4549250125805 |
| Inside diameter  | 260 mm        |
| Outside diameter | 360 mm        |
| Thickness        | 63.5 mm       |
| Weight           | 18900 g       |
| Packaging        | 1             |

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE