


## Tapered roller bearing 4580-4535-JTEKT - 4580-4535-KOYO

<https://www.123bearing.ie/bearing-housing/roller-bearing/tapered/4580-4535-koyo>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
d	D	T	B	C	r <sub>1</sub>	r <sub>2</sub>	C <sub>r</sub>	C <sub>10</sub>	Grease lub.	Oil lub.
50.800	104.775	39.688	40.157	33.338	3.6	3.2	151	211	3 800	5 100

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer to)	
Inner ring	Outer ring	a	d <sub>a</sub>	d <sub>b</sub>	D <sub>a</sub>	D <sub>b</sub>	r <sub>a</sub> max.	r <sub>b</sub> max.	e	Y <sub>1</sub>	Y <sub>2</sub>	Inner ring	Outer ring
4580	4535	27.3	67.0	61.0	90.0	99.0	3.6	3.2	0.34	1.79	0.98	1.06	0.576

### PRODUCT FEATURES

Brand	JTEKT
N° Ean13	3663952427775
Inside diameter	50.8 mm
Outside diameter	104.775 mm
Thickness	39.688 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE