


Cam follower CF10-VM-IKO - CF10-VM-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cf10-vm-iko>



CAM FOLLOWERS

Standard Type Cam Followers Full Complement Type/With Screwdriver Slot



| Stud dia. mm | Identification number | | | | | | | | CF-V | | | | | |
|------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|-------------------------|-----------------------------|--------------------------------|---|---------------------------------------|-------------------------------------|---|---|
| | Shield type | | | | Sealed type | | | | g | D | C | d ₁ | | |
| | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | With crowned outer ring | With cylindrical outer ring | | | | | | |
| 10 | | CF 10 | VM | | | | | | 46 | 22 | 12 | 10 | | |
| Boundary dimensions mm | | | | | | | | | | | | | | |
| G | G ₁ | B _{max} | B _{1 max} | B ₂ | B ₃ | C ₁ | g ₁ | g ₂ | f ⁽¹⁾ Min. mm | Mounting diameter f ⁽¹⁾ mm | Maximum tightening torque C N·m | Basic dynamic load rating C N | Basic static load rating C ₀ N | Maximum allowable static load C ₁₀ N |
| M10×1 | 12 | 13.2 | 36.2 | 23 | — | 0.6 | *4 | — | 0.3 | 16 | 14.7 | 9 570 | 14 500 | 8 650 |

PRODUCT FEATURES

| | |
|------------------|---------------|
| Brand | IKO |
| N° Ean13 | 3663952440262 |
| Inside diameter | 10 mm |
| Outside diameter | 22 mm |
| Thickness | 12 mm |
| Packaging | 1 |

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE