


Cam follower CF8-UUM-IKO - CF8-UUM-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cf8-uum-iko>



CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Mass (Ref.)																																										
	Shield type		Sealed type		g	D	C	d ₁	G																																						
B	With crowned outer ring	With cylindrical outer ring	With tapered outer ring	With cylindrical outer ring	28.5	19	11	B	M 8×1																																						
<table border="1"> <thead> <tr> <th colspan="10">Boundary dimensions mm</th> </tr> <tr> <th>G₁</th> <th>B</th> <th>B₁</th> <th>B₂</th> <th>B₃</th> <th>C₁</th> <th>g₁</th> <th>g₂</th> <th>r_smax (°)</th> <th>f Min. mm</th> <th>Maximum ignoring stress N·m</th> <th>Ball dynamic load rating C N</th> <th>Ball static load rating C₀ N</th> <th>Maximum allowable static load N</th> </tr> </thead> <tbody> <tr> <td>10</td> <td>12.2max</td> <td>32.2max</td> <td>20</td> <td>—</td> <td>0.6</td> <td>*4</td> <td>—</td> <td>0.3</td> <td>13</td> <td>7.1</td> <td>4 250</td> <td>4 740</td> <td>4 620</td> </tr> </tbody> </table>										Boundary dimensions mm										G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N	10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	7.1	4 250	4 740	4 620
Boundary dimensions mm																																															
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm	Maximum ignoring stress N·m	Ball dynamic load rating C N	Ball static load rating C ₀ N	Maximum allowable static load N																																		
10	12.2max	32.2max	20	—	0.6	*4	—	0.3	13	7.1	4 250	4 740	4 620																																		

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441061
Inside diameter	8 mm
Outside diameter	19 mm
Thickness	11 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE