


Cam follower CF10-1-UUM-IKO - CF10-1-UUM-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cf10-1-uum-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



CF-UU

Stud dia. mm	Identification number				Max (Ref.)				
	Shield type		Sealed type		g	D	C	d ₁	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
10					60	26	12	10	M10×1

Boundary dimensions mm													
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _{max} ^(*)	f _{Min.} mm	Maximum ignoring stress C	Ball dynamic load rating C ₀	Ball static load rating C ₀	Maximum allowable static load N
12	13.2max	36.2max	23	—	0.6	*4	—	0.3	16	14.7	5 430	6 890	6 890

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441238
Inside diameter	10 mm
Outside diameter	26 mm
Thickness	12 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE