


## Cam follower CF30-R-IKO - CF30-R-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cf30-r-iko>



### CAM FOLLOWERS

Standard Type Cam Follower **With Cage/With Screwdriver Slot**



Stud dia. mm	Identification number				Maxs (Ref.)				
	Shield type		Sealed type		g	D	C	d <sub>1</sub>	G
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30	CF 30	R			1 870	80	35	30	M30×1.5

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum tightening torque N·m	Ball dynamic load rating C N	Ball static load rating C <sub>0</sub> N	Maximum allowable static load N	
G <sub>1</sub>	B	B <sub>1</sub>	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	r <sub>max</sub> <sup>(*)</sup>	r <sub>min</sub>						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441566
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	35 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE