

Cam follower CF30-UUR-IKO - CF30-UUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cf30-uur-iko>

IKO

CAM FOLLOWERS

Standard Type Cam Followers With Cage/With Screwdriver Slot



Stud dia. mm	Identification number				Mass (Ref.) g	D	C	d ₁	G
	Shield type		Sealed type						
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring					
30	CF 30 UUR				1 870	80	35	30	M30×1.5

Boundary dimensions mm										Mounting torque N·m	Ball dynamic load rating C	Ball static load rating C ₀	Maximum allowable static load N		
G ₁	B	B ₁	B ₂	B ₃	C ₁	g ₁	g ₂	r _s max (°)	f Min. mm						
32	37	max	100	max	63	15	1	8	4	1	49	438	45 400	85 100	85 100

PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952441580
Inside diameter	30 mm
Outside diameter	80 mm
Thickness	35 mm
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE