

## Cam follower CFE30-2-B-IKO - CFE30-2-B-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe30-2-b-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Hexagon Hole



CFE-B

Outside diameter of outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		Ø	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
41	CFE 30-2 B				2 380	90	35	41

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N	
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1 max</sub>	B <sub>2</sub>	C <sub>1</sub>	G <sub>1</sub>	H	H <sub>1 max</sub>	Excentricity e						
M30×1.5	32.5	37	100	63	1	8	30.5	17	1	1.5	49	438	45 400	85 100	85 100

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459695
Inside diameter	41 mm
Outside diameter	90 mm
Thickness	35 mm
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE