


Cam follower CFE10-1-UUR-IKO - CFE10-1-UUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe10-1-uur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number					Mass (Ref.)		
	Shield type		Sealed type		ø	D	C	d ₂
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
13	CFE 10-1 UUR				65	26	12	13

Boundary dimensions mm										Essentiality g	Mounting dimension f mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
G	B ₃	B max	B ₁ max	B ₂	C ₁	G ₁	(1) r _{max}	e	ε						
M10×1.25	10.5	13.2	36.2	23	0.6	*4	12.5	0.3	0.4	16	13.8	5 430	6 890	6 890	

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459862
Inside diameter	13 mm
Outside diameter	26 mm
Thickness	12 mm
Weight	65 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE