

Cam follower CFE12-UU-IKO - CFE12-UU-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe12-uu-iko>

IKO
CAM FOLLOWERS
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**

Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)									
	Shield type		Sealed type		\emptyset	D	C	d_2						
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 12 UU	105	30	14	16					
Boundary dimensions mm														
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	G ₁	(¹) r _{max}	Mounting dimension f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable axial load N		
M12×1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	7 910	9 790	9 790

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459916
Inside diameter	16 mm
Outside diameter	30 mm
Thickness	14 mm
Weight	105 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE