


Cam follower CFE12-1-UUR-IKO - CFE12-1-UUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe12-1-uur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		\emptyset	D	C	d_2
16	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	115	32	14	16
	CFE 12-1 UUR							

Boundary dimensions mm														
G	B ₃	B ₁ max	B ₁ min	B ₂	C ₁	G ₁	G ₂	Mounting dimension f Min. mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable axial load N		
M 8×1.25	9.5	12.2	32.2	20	0.6	*4	10.5	0.3	0.4	13	6.5	4 250	4 740	4 620

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060459947
Inside diameter	16 mm
Outside diameter	32 mm
Thickness	14 mm
Weight	115 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE