


## Cam follower CFE20-IKO - CFE20-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe20-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers **With Cage/With Screwdriver Slot**



Outside diameter of eccentric roller mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		$\emptyset$	D	C	$d_2$
27	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	500	52	24	27
<b>CFE 20</b>								

Boundary dimensions mm										Essentiality	Mounting dimension $f$ mm	Maximum tightening torque N-m	Basic dynamic load rating C N	Basic static load rating $C_0$ N	Maximum allowable static load N
G	$B_3$	$B$ max	$B_1$ max	$B_2$	$C_1$	$G_1$	$r_{max}$	$r_{min}$	$r$						
M20 X 1.5	19.5	25.6	66.1	40.5	0.8	8	21	1	0.8	34	119	20 700	34 600	34 600	

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460042
Inside diameter	27 mm
Outside diameter	52 mm
Thickness	24 mm
Weight	500 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE