

## Cam follower CFE24-1-UU-IKO - CFE24-1-UU-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe24-1-uu-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers With Cage/With Screwdriver Slot



Outside diameter of eccentric roller mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d <sub>2</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	CFE 24-1 UU					
33							1 220	72	29	33

  

Boundary dimensions mm										Essentiality g	Mounting dimension f mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G	B <sub>3</sub>	B max	B <sub>1</sub> max	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	(1) r <sub>max</sub>	e						
M24×1.5	25.5	30.6	80.1	49.5	0.8	8	24	1	0.8	40	215	30 500	52 600	52 000	

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3663952816524
Inside diameter	33 mm
Outside diameter	72 mm
Thickness	29 mm
Weight	1220 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE