


Cam follower CFE10-VBUU-IKO - CFE10-VBUU-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe10-vbuu-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



CFE-VBUU

Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)					
	Shield type			Sealed type			Ø	D	C	d _e		
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring								
13							CFE 10	VBUU	50.5	22	12	13

Boundary dimensions mm															
G	B ₃	B ₁ max	B ₂ max	B ₂	C ₁	g ₁	G ₁	H	f _{max} Eccentricity	f Mounting dimension Min. mm	Maximum springing torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N	
M10×1.25	10.5	13.2	36.2	23	0.6	—	12.5	4	0.3	0.4	16	13.8	9 570	14 500	8 650

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460394
Inside diameter	13 mm
Outside diameter	22 mm
Thickness	12 mm
Weight	50.5 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE