

## Cam follower CFE10-1-VBUUR-IKO - CFE10-1-VBUUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe10-1-vbuur-iko>

**IKO**  
**CAM FOLLOWERS**

Eccentric Type Cam Followers **Full Complement Type/With Hexagon Hole**

CFE10-1-VBUUR

Outside diameter of outer ring mm	Identification number						Mass (Ref.)		
	Shield type		Sealed type		g	D	C	d <sub>e</sub>	
13	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring	66	26	12	13	
<b>CFE 10-1 VBUUR</b>									

  

Boundary dimensions mm										
G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	C <sub>1</sub>	G <sub>1</sub>	g <sub>1</sub>	H	f <sub>max</sub>	f	Mounting dimension
M10 × 1.25	10.5	13.2	36.2	23	0.6	—	12.5	4	0.3	0.4
Maximum splining torque: 13.8 N·m Basic dynamic load rating: 9 570 N Basic static load rating: 14 500 N Maximum allowable static load: 8 650 N										

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460431
Inside diameter	13 mm
Outside diameter	26 mm
Thickness	12 mm
Weight	66 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE