


Cam follower CFE16-VBUUR-IKO - CFE16-VBUUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe16-vbuur-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of outer ring mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
22	CFE 16 VBUUR						193	35	18	22

Boundary dimensions mm															
G	B ₃	B ₁ max	B ₂ max	C ₁	G ₁	H	H _{max} (*)	f mm	Mounting dimension mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N		
M16×1.5	15.5	19.6	52.1	32.5	0.8	6	17	6	0.6	0.8	26	58.5	20 700	37 600	23 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460554
Inside diameter	22 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	193 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE