

## Cam follower CFE30-VB-IKO - CFE30-VB-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe30-vb-iko>

IKO

### CAM FOLLOWERS

Eccentric Type Cam Followers Full Complement Type/With Hexagon Hole



Outside diameter of eccentric collar mm	Identification number						Mass (Ref.)			
	Shield type			Sealed type			Ø	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring						
41	CFE 30 VB						2 030	80	35	41

  

Boundary dimensions mm															
G	B <sub>3</sub>	B <sub>1</sub> max	B <sub>2</sub> max	C <sub>1</sub>	G <sub>1</sub>	H	H <sub>1</sub> ( <sup>1</sup> )	Eccentricity g	Mounting dimension f Min. mm	Maximum splining torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N		
M30×1.5	32.5	37	100	63	1	8	30.5	17	1	1.5	49	438	67 700	144 000	85 900

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060460776
Inside diameter	41 mm
Outside diameter	80 mm
Thickness	35 mm
Weight	2030 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE