

## Cam follower CFE12-1-VR-IKO - CFE12-1-VR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe12-1-vr-iko>

**IKO**  
**CAM FOLLOWERS**  
Eccentric Type Cam Followers Full Complement Type/With Screwdriver Slot

Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.) g	D	C	da
	Shield type		Sealed type					
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
16	CFE 12-1 VR				117	32	14	16

  

Boundary dimensions mm										Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1max</sub>	B <sub>2</sub>	C <sub>1</sub>	B <sub>1</sub>	G <sub>1</sub>	r <sub>1min</sub>	E					
M12 × 1.5	11.5	15.2	40.2	25	0.6	6	13.5	0.6	0.8	21	21.9	13 500	19 700	13 200

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461056
Inside diameter	16 mm
Outside diameter	32 mm
Thickness	14 mm
Weight	117 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE