

Cam follower CFE16-V-IKO - CFE16-V-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe16-v-iko>

IKO

CAM FOLLOWERS

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**



Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d _e
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
22	CFE 16 V				193	35	18	22

Boundary dimensions mm														
G	B ₃	B _{max}	B ₁ max	B ₂	C ₁	g ₁	G ₁	r ₁ min	Eccentricity E	Mounting diameter f Min. mm	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N	Maximum allowable static load N
M16 × 1.5	15.5	19.6	52.1	32.5	0.8	6	17	0.6	0.8	26	58.5	20 700	37 600	23 200

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461100
Inside diameter	22 mm
Outside diameter	35 mm
Thickness	18 mm
Weight	193 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE