

## Cam follower CFE30-2-VUUR-IKO - CFE30-2-VUUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cfe30-2-vuur-iko>

**IKO**  
**CAM FOLLOWERS**

Eccentric Type Cam Followers **Full Complement Type/With Screwdriver Slot**

E-500

CFE -- VUUR

Outside diameter of eccentric outer ring mm	Identification number				Mass (Ref.)			
	Shield type		Sealed type		g	D	C	d <sub>e</sub>
	With crowned outer ring	With cylindrical outer ring	With crowned outer ring	With cylindrical outer ring				
<b>41</b>	<b>CFE 30-2 VUUR</b>				2 380	90	35	41

  

Boundary dimensions mm											Eccentricity E	Mounting dimension f Min. mm	Maximum operating torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N	Maximum allowable static load N
G	B <sub>3</sub>	B <sub>max</sub>	B <sub>1</sub> max	B <sub>2</sub>	C <sub>1</sub>	g <sub>1</sub>	G <sub>1</sub>	r <sub>1</sub> min	r <sub>2</sub> min	r <sub>3</sub> min						
M30 × 1.5	32.5	37	100	63	1	8	30.5	1	1.5	49	438	67 700	144 000	85 900		

### PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060461407
Inside diameter	41 mm
Outside diameter	90 mm
Thickness	35 mm
Weight	2380 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE