


Cam follower CR14-BUUR-IKO - CR14-BUUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cr14-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				g	Mass (Ref.)					
	Shield type		Sealed type			D	C	d ₁	G _{UNF}	G ₁	
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
9.525 ($\frac{3}{8}$)	CR 14 BUUR				46	22.225 ($\frac{7}{8}$)	12.700 ($\frac{1}{2}$)	9.525 ($\frac{3}{8}$)	$\frac{1}{4}$ -24	9.525 ($\frac{3}{8}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm (mm/inch)	Maximum tightening torque C	Basic dynamic load rating C	Basic static load rating C ₀
14.2 (0.56)	22.225 ($\frac{7}{8}$)	6.350 ($\frac{1}{4}$)	0.794 ($\frac{1}{32}$)	4.762 ($\frac{3}{16}$)	2.381 ($\frac{3}{32}$)	4.762 ($\frac{3}{16}$)	0.794 ($\frac{1}{32}$)	15.081 ($\frac{5}{8}$)	10.6	4 790	5 970

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462466
Inside diameter	9.525 mm
Outside diameter	22.225 mm
Thickness	12.7 mm
Weight	46 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE