


Cam follower CR20-BUUR-IKO - CR20-BUUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cr20-buur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers With Cage/With Hexagon Hole



Stud dia. mm (inch)	Identification number				Mass (Ref.)						
	Shield type		Sealed type			g	D	C	d ₁	G UNF	G ₁
	With covered outer ring	With cylindrical outer ring	With covered outer ring	With cylindrical outer ring							
12.700 ($\frac{1}{2}$)	CR 20 BUUR				132	31.750 ($\frac{1}{2}$)	19.050 ($\frac{3}{4}$)	12.700 ($\frac{1}{2}$)	J ₁ -20	15.875 ($\frac{5}{8}$)	
Boundary dimensions mm/inch											
B	B ₂	B ₃	C ₁	E ₁	E ₂	H	r	Bearing dimension f Mm/ mm(inch)	Maximum tightening torque C	Basic dynamic load rating N	Basic static load rating C ₀ N
20.4 (3/4)	31.750 ($\frac{1}{2}$)	7.838 ($\frac{5}{16}$)	0.794 ($\frac{1}{16}$)	4.782 ($\frac{3}{8}$)	3.175 ($\frac{1}{4}$)	6.350 ($\frac{1}{4}$)	1.588 ($\frac{1}{16}$)	21.828 ($\frac{7}{8}$)	27.7	14 200	16 000

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060462558
Inside diameter	12.7 mm
Outside diameter	31.75 mm
Thickness	19.05 mm
Weight	132 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE