

Cam follower CR8-V-IKO - CR8-V-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cr8-v-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sealed type		ϕ	D	C	d_1	G UNF	G_1
	With cover	With cylindrical outer ring	With shielded outer ring	With cylindrical outer ring						
4.826		CR 8 V			9	12.700	8.731	4.826	No.10-32	6.350

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C_0 N
B max	B_2	B_3	C_1	g_1	g_2	r				
15.2(0.40)	12.7(0.50)	- (-)	0.794(0.031)	1.175(0.046)	- (-)	0.387(0.015)	0.324(0.013)	1.4	4 200	4 750

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463098
Inside diameter	4.826 mm
Outside diameter	12.7 mm
Thickness	8.731 mm
Weight	9 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE