


Cam follower CR16-VUUR-IKO - CR16-VUUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cr16-vuur-iko>

IKO

CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inch)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		g	D	C	d ₁	G	G ₁
	With coverd outer ring	With cylindrical outer ring	With drilled outer ring	With cylindrical outer ring				UNF		
11.112 ($\frac{7}{16}$)				CR 16 VUUR	74	25.400 ($\frac{1}{1}$)	15.875 ($\frac{3}{2}$)	11.112 ($\frac{7}{16}$)	$\frac{3}{8}$ -20	12.700 ($\frac{1}{2}$)
Boundary dimensions mm(inch)					Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C ₀ N		
B max	B ₂	B ₃	C ₁	g ₁					g ₂	r
17.3.0.00	25.400 ($\frac{1}{1}$)	8.350 ($\frac{1}{2}$)	0.794 ($\frac{1}{4}$)	4.762 ($\frac{3}{4}$)	3.175 ($\frac{1}{4}$)	1.191 ($\frac{1}{4}$)	17.668 ($\frac{3}{4}$)	17.4	13 100	22 700

PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463562
Inside diameter	11.112 mm
Outside diameter	25.4 mm
Thickness	15.875 mm
Weight	74 g
Packaging	1

contact@123bearing.ie

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE