


## Cam follower CR26-VUUR-IKO - CR26-VUUR-IKO

<https://www.123bearing.ie/bearing-housing/deep-groove-bearing/cam-follower/cr26-vuur-iko>

IKO

### CAM FOLLOWERS

Inch Series Cam Followers Full Complement Type/With Screwdriver Slot



Stud dia. mm (inchi)	Identification number				Mass (Ref.)					
	Shield type		Sleeved type		g	D	C	d <sub>1</sub>	G	G <sub>1</sub>
	With covered outer ring	With cylindrical outer ring	With ribbed outer ring	With cylindrical outer ring						
15.875 ( $\frac{5}{8}$ )			CR 26	VUUR	265	41.275 ( $\frac{1}{2}$ )	22.225 ( $\frac{7}{8}$ )	15.875 ( $\frac{5}{8}$ )	$\frac{1}{2}$ -18	18.050 ( $\frac{7}{8}$ )

Boundary dimensions mm(inch)							Mounting dimension f Min. mm(inch)	Maximum tightening torque N·m	Basic dynamic load rating C N	Basic static load rating C <sub>0</sub> N
B max	B <sub>2</sub>	B <sub>3</sub>	C <sub>1</sub>	g <sub>1</sub>	g <sub>2</sub>	r				
23.8 (0.94)	38.100 (1.5)	9.525 ( $\frac{3}{8}$ )	0.794 ( $\frac{1}{4}$ )	4.762 ( $\frac{3}{8}$ )	3.969 ( $\frac{5}{16}$ )	1.588 ( $\frac{1}{4}$ )	26.166 (1.0)	55.7	28 200	40 100

## PRODUCT FEATURES

Brand	IKO
N° Ean13	3616060463968
Inside diameter	15.875 mm
Outside diameter	41.275 mm
Thickness	22.225 mm
Weight	265 g
Packaging	1

[contact@123bearing.ie](mailto:contact@123bearing.ie)

+33 359 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE